

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : G06F 17/60	A1	(11) International Publication Number: WO 99/45486 (43) International Publication Date: 10 September 1999 (10.09.99)
----------------------------------------------------------------	----	-----------------------------------------------------------------------------------------------------------------------------

(21) International Application Number: PCT/EP99/01346 (22) International Filing Date: 2 March 1999 (02.03.99) (30) Priority Data: 09/033,840 3 March 1998 (03.03.98) US (71) Applicant (<i>for all designated States except US</i>): SAP AK-TIENGESELLSCHAFT [DE/DE]; Neurottstrasse 16, D-69190 Walldorf (DE). (72) Inventor; and (75) Inventor/Applicant (<i>for US only</i>): SÖHNER, Volkmar [DE/DE]; Am Hohenstein 17a, D-74889 Sinsheim (DE). (74) Agents: PFEIFER, Hans-Peter et al.; Beiertheimer Allee 19, D-76137 Karlsruhe (DE).	(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

(54) Title: METHOD FOR COMPUTERIZED SUPPLY CHAIN PLANNING



(57) Abstract

A data model for a supply chain is provided whereby individual working steps in a production process are defined as activities, and organized groups of such activities are defined as orders. Activities are allocated to no more than one resource and contain information concerning the start and finish time for the activity, any resource on which the activity is currently scheduled, and a list of alternative resources, if any. Activities are linked to each other via auxiliary objects, which contain information concerning the minimum and maximum time between activities. Orders may contain input and/or output interface nodes, representing the materials consumed and produced by the order. Each output interface node representing a quantity of material created from one order is linked via an auxiliary object to respective input interface node or nodes form other orders that are scheduled to receive that material. Order anchors are defined whereby a planning algorithm can easily reference an order by its order number in a database table. Planning algorithm can easily reference an order by its order number in a database table. Planning object anchors allow the planning algorithm to access all the orders for a given material, and resource anchors permit access to all activities scheduled for that resource.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

METHOD FOR COMPUTERIZED SUPPLY CHAIN PLANNING

Background of the invention

Supply chain planning ("SCP"), which comprises the logistical plan of an in-house supply chain, is essential to the success of many of today's manufacturing firms.

Most manufacturing firms rely on control of their production plants using computerized supply chain planning in some form to ensure the timely delivery of products in response to customer demands. Typically, supply chain planning is hierarchical in nature, extending from distribution and production planning driven by customer orders, to materials and capacity requirements planning, to shop floor scheduling, manufacturing execution, and deployment of products.

Supply chain planning ensures the smooth functioning of different aspects of production, from the ready supply of components to meet production demands to the timely transportation of finished goods from the factory to the customer.

The modern supply chain often encompasses a vast array of data. The planning applications that create and dynamically revise plans in the supply chain in response to changing demands and capacity require rapid access to data concerning the flow of materials through the supply chain. The efficient operation of the supply chain depends upon the ability of the various plans to adjust

to changes, and the way in which the required data is stored determines the ease with which it can be accessed.

In the conventional relational model, supply chain data is stored in multiple relational database tables. If a parameter of a manufacturing order is changed, all of the aspects of the supply chain affected by such change must be re-calculated using the relational tables. Before a planning algorithm can change the date and/or quantity of a manufacturing order in response to changing capacities, for example, it must take into account the effect that the date and/or quantity change will have on other production and sales orders. Such a calculation is very complex, and requires that the algorithm have access to data concerning all the other orders, materials and resources that would be affected by the change. In the conventional model that information must be calculated by tracing through relational database tables. Such calculations are cumbersome and delay planning functions unnecessarily.

There is therefore a need for all data relevant to supply chain planning to be made available by a computerized method in the most efficient and usable manner possible so as to reduce drastically the runtime of the planning functions, thus allowing the required control of production processes with given computer resources in an improved manner.

Summary of the invention

To cope with this need the present invention relates to a data model for storing objects that are relevant for planning the logistical processes along the entire supply

chain of a company. A data structure is defined whereby individual working steps in the production process are defined as activities, and organized groups of such activities are defined as orders. Activities are allocated to no more than one resource, if any, and contain information concerning the start and finish time for the activity, any resource on which the activity is currently scheduled, and a list of alternative resources, if any. Activities representing a time calculation only are not required to correspond to a resource. Activities are linked to each other via auxiliary objects, which contain information concerning the minimum and maximum time between activities. Orders may contain input and/or output interface nodes, representing the materials consumed and produced by activities within the order. An output interface node representing a quantity of material created from one order is linked via an auxiliary object to respective input interface node or nodes from other orders that require that material. Order anchors are defined whereby a planning algorithm can easily reference an order in the data structure by its order number in a database table. Planning object anchors allow the planning algorithm to access all the orders for a given material, and resource anchors permit access to all activities scheduled for that resource.

More specifically the invention provides a method for computerized supply chain planning, comprising a data model, said data model comprising at least one order which comprises at least one activity, wherein each of said at least one activity represents a working step that is indivisible from a production planning perspective; each of said at least one activity is linked to a reference to all immediately subsequent activities of said order; and each of said at least one activity is

linked to a reference to all immediately preceding activities of said order.

Preferred embodiments are defined in the subclaims.

In summary, the following features and achievements of supply chain planning using the instant data model may be noted:

The invention allows to store manufacturing process data so as to provide planning algorithms and applications programs with the most efficient access possible to the data that they require.

The data are stored in a logical manner that reflects the progress of materials and orders along the supply chain.

Discrete data elements representing individual working steps in the production process are defined, and the relationships between said elements are stored.

Specific information about each working step is linked with those data elements, including the start time, finish time, and the resources upon which the working step is performed or alternatively may be performed.

Groups of working steps in the manufacturing process are organized as objects that can be accessed by planning algorithms, and the relationships between said groups of working steps are stored.

A planning algorithm has efficient access to any organized group of working steps in the production process by providing a database table whereby each of the

groups of working steps is referenced to its location in the data structure.

A planning algorithm also has efficient access to the working step performed by a given resource at a specific time, by providing a database table whereby the dates and times of all working steps performed by each resource are referenced to that resource.

A planning algorithm furthermore has efficient access to organized groups of working steps involved in creating or consuming a specific material, by providing a database table whereby information identifying the material is referenced to the input or output of each such organized group of working steps.

Brief Description of the Drawings

Figure 1 is a representation of the relationship between an order and its activities.

Figure 2 is a representation of the fusing of activities to make operations.

Figure 3 is a representation of the input and output interface nodes of an order.

Figure 4 is a representation of input activities, output activities, and activities with no input or output.

Figure 5 is a representation of how temporal constraints between activities are modeled.

Figure 6 is a representation of how temporal constraints between orders are modeled.

Figure 7 is a representation of a simple order network with pegging.

Figure 8 is a representation of how pegging between orders is modeled.

Figure 9 is a representation of an order anchor and an operation anchor.

Figure 10 is a representation of a planning object anchor.

Figure 11 is a representation of a resource anchor.

Detailed Description of the Drawings

As shown in Figure 1, an order 10 represents an organizational unit that may group together several activities 11. Each order points to the first activity and the last activity of its activity network. Thus, order 10 points to activity 12 and activity 13. Each activity 11 contains a reference 14 to its order. As depicted in Figure 2, related activities such as a chain of activities 11a, 11b, and 11c that must be executed in order may be grouped together into an "operation" 20 to avoid having to map each activity individually on a planning table.

An order, such as order 10, may have one or more input interface nodes 30 and/or one or more output interface nodes 31, as shown in Figure 3. Each input interface node

30 represents one material. An input interface node also has attributes containing information as to the quantity of the material required, the time requirement of the material, and the shortage of that material, which is derived from the difference between the quantity of material required and the quantity that it delivered by other orders or stock. Each output interface node 31 has similar attributes, such as type of material created, the quantity of the material, the time availability of the material, and the surplus of that material, which is derived from the quantity of material produced that is not yet delivered to other orders. Each input interface node 30 may refer to the activity 12, if any, in which the material that it represents is consumed, and each output interface node 31 points to the activity 13, if any, in which the material that it represents is created. If an activity 12 consumes a material, all input materials of this activity can be traced via arrow marked with dashes and dots 32a that points from activity 12 to input interface node 30. If input activity 12 consumes more than one material, arrow 32b joins input interface node 30a to the next input interface node 30b, which links on the same input activity 12. The chain of input interface nodes 30, which can have an infinite length, allows to ascertain which materials are required for the order in question, which means that the bill of materials for the output materials can be determined. Similarly, the output materials of an activity can be traced via arrow marked with dashes and dots 34 joining the activity with the first output interface node 31 of the activity 13. If there are several output materials, then an arrow 33 joins output interface node 31a to the next output interface node 31b, which represents the second material created. Like the input interface nodes 30, this chain can have an infinite length.

Figure 4 illustrates order 10 having activities 41 with no input or output materials, and also activities such as assembly process 42 that both consume and create materials. Stock or a purchase order of a material is modeled by an order with one output interface node 31 and with no input interface nodes or activities. If the capacity of the vendor is to be taken into account in modeling a purchase order, however, the purchase order must contain at least one activity representing the available capacity of the vendor (as accurately as possible). A plurality of purchase orders may be grouped into a "schedule line", which is modeled as a purchase order with several output interface nodes, each with a different delivery time. Customer requirements mirror purchase orders: each order has one input interface node 30, but no output interface nodes or activities. Orders that consume materials such as customer orders are modeled as "issuing elements", while orders that create materials are modeled as "receiving elements", allowing both types of orders to be modeled as objects similar to other components in the SCP model, thereby saving the need to create additional algorithms to operate on the model. An order without input or output interface nodes may exist, for example, as an order representing a test or maintenance on a resource.

Links may also be created between successive activities, said links containing references not only to successor activities, but also to the minimum and maximum time between activities. These temporal constraints can exist both between activities in the same order (intra-order constraints), and between activities belonging to different orders (cross-order constraints).

Figure 5 illustrates intra-order temporal constraints between activities. As shown in Figure 5a, activity 11d has three successor activities 11e, 11f, and 11g. Edges 50, 51 and 52 representing the temporal constraints have attributes, which are the minimum and maximum time interval between activities, and the type of temporal constraint, such as start-start, start-finish, finish-finish, or finish-start. References to successive activities are modeled by following the full and dashed straight arrows. In Figure 5b, starting from activity 11d, first follow the arrow "succ_edge" 51 to reach the first successor activity from the small square 53 along the edge "succ_act" 52. This process is repeated from the first small square in order to reach all other successor activities successively. The small squares 53 are symbols of auxiliary objects, which store the references to the successor activities, the next auxiliary object, and all the attributes of the temporal constraint between activities. The same technique can be used to model predecessor constraints, for example by following the curved arrows "pred_edge" 54 and "pred_act" 55 to find the predecessors of activity 11h.

Cross-order temporal constraints are illustrated in Figure 6. A first order 61 and a second order 62 each contain three activities 11. There is a cross-order temporal constraint between activity 11j of first order 61 and activity 11n of second order 62. This constraint is mapped in the same way as described above for an intra-order temporal constraint, showing that activity 11j has successor activities 11k and 11o, and that activity 11o has predecessor activities 11j and 11n.

Similarly, "pegging" links two orders wherein one of the orders supplies a material consumed by the other order. Pegging tracks the type and quantity of material supplied by one order (the "subordinate order") to another order (the "superior order"). Pegging allows to ascertain the superior and subordinate orders for any given order at any given time. If the dates of an order are rescheduled, pegging allows all other orders influenced by this change to be updated.

Figure 7 illustrates an example of pegging between orders, consisting of five orders 71, 72, 73, 74 and 75 that produce or consume materials M1, M2 and/or M3. As shown, for example, one piece each of M2 and M3 is required to produce M1. Next to each input interface node 30 respective attributes are shown which are the required quantity and the requirements date. Next to each output interface 31 node the shown attributes are the quantity created and the availability date. For example, order 71 produces 100 M2, which is sufficient to satisfy the demands of orders 72 and 73 producing M1. The demand of order 73 is satisfied by orders 71 and 75.

As shown in Figure 8, relationships between orders are mapped in the same manner as are temporal constraints between activities. The orders which M2 order 71 supplies can be found by starting from output interface node 31 of the M2 order 71 and alternately following the full straight arrows ("succ_edge") 51 and the dashed straight arrows ("succ_act") 52. Similarly, the orders that supply M1 order 73 can be found by starting from the input interface nodes 30 of M1 order 73, and alternately following the full curved arrows ("pred_edge") 54 and dashed arrows ("pred_output") 55 to output interface node 31 of the supplying orders 71 and 75.

While pegging can link a large network of orders, not all orders have relationships to each other. Accordingly, the SCP network is usually a collection of disjunctive sub-networks, making it difficult to scan the whole network to locate a specific order. Accordingly, an "order anchor" 90 as shown in Figure 9 can provide direct access to an order 10 or group of orders in the SCP network via an "order number" 91. This information is preferably stored in a RAM-buffered relational database table with a primary index for the order number and a secondary index for the reference to the order in the network, or object identity ("OID") 92. Similarly, an "operation anchor" 93 can provide direct access to an operation 20, or fused activities, within an order 10. The key 97 of the operation anchor 93 is the OID 92 for order 10, which is referenced to the predetermined operation number 94, an operation number within that order 95, and the first activity 96 of the respective operation 20. So for an application program to access a certain operation 20 of an order 10, it must first use the order anchor 90 to determine the OID 92 for the order, then use the operation anchor 93 to find the first activity 96 of the operation 20 that it is seeking.

Planning object anchors 100, illustrated in Figure 10, enable an application program to determine efficiently all the orders 10 for a given material. Each material is identified in a relational database table according to its material number 101, plant 102, storage location 103, and batch 104, collectively designated as a "planning object". Planning object anchors in table 109 reference to first input interface node 105 for material M4, and first output interface node 106 for material M1. All input interface nodes 30 and output interface nodes 31 of

each material are kept in doubly concatenated lists which are sorted according to requirements and availability dates, as shown in Figure 10. Thus, it is possible to select all receiving and issuing elements for each material or "planning object", which can be important for materials requirements planning.

Since each activity preferably corresponds to one specific resource, a resource anchor is provided to enable an application program to determine all activities for a specific resource. Figure 11 depicts a resource anchor 110 modeled as a relational database table 119 that references each resource number 111 to the corresponding first activity A2 112 scheduled on that resource. The first activity A2 112 is then linked to the next activity A3 113 scheduled on the same resource, which is in turn linked to subsequent activities A5 115 and A8 118 in chronological order according to schedule time. This facilitates the scheduling of new activities on particular resources. For example, in order to schedule a new activity on a resource, an application program must first check the activity immediately before and the activity immediately after the proposed time for the new activity to determine whether there is sufficient time to perform the new activity on that resource. Since resource anchor 110 stores all activities of a particular resource chronologically referenced to that resource, this information is easily and rapidly accessible to an applications program.

Claims

1. Method for computerized supply chain planning, comprising a data model, said data model comprising at least one order which comprises at least one activity, wherein:
 - each of said at least one activity represents a working step that is indivisible from a production planning perspective;
 - each of said at least one activity is linked to a reference to all immediately subsequent activities of said order; and
 - each of said at least one activity is linked to a reference to all immediately preceding activities of said order.
2. The method of claim 1, wherein said at least one order comprises at least one of
 - one or more input interface nodes, wherein each input interface node represents a material consumed by said at least one order, each input interface node being linked to all activities that consume said material; and
 - one or more output interface nodes, wherein each output interface node represents a material created by said at least one order, each output interface node being linked to all activities that create said material.

3. The method of claim 1, wherein said data model comprises a plurality of orders and each output interface node of a first order is linked to a reference to a respective input interface node of each subsequent order scheduled to consume the material associated with said output interface node of said first order.
4. The method of any one of claims 1 to 3, wherein said data model comprises an order in which said reference to all immediately preceding activities and said reference to all immediately subsequent activities each have at least two attributes, said at least two attributes including (i) the minimum and maximum time interval between activities and (ii) the type of temporal constraint.
5. The method of any one of claims 1 to 4, wherein said data model comprises an order in which each of said at least one activity has at least four attributes, said at least four attributes including (i) a start and (ii) finish time, a (iii) reference to the resource on which the activity is currently scheduled, and (iv) a reference to a list of one or more alternative resources.
6. The method of any one of claims 2 to 5, wherein said data model comprises an order in which each input interface node contains information regarding a required material, required quantity, the time at which said required material is required, and any shortage of said required material, said shortage defined as the difference between the required quantity and the quantity of said required material that is delivered by other orders or stock, and

wherein each output interface node contains information regarding a created material, created quantity, the time at which said created material is created, and any surplus of said created material, said surplus defined as the difference between the created quantity and the quantity of said created material that is not yet delivered to other orders.

7. The method of any one of claims 1 to 6, wherein said data model comprises a plurality of orders which have pre-assigned order numbers, said data model further comprising a database table having an entry for each pre-assigned order number matched to its object identity, which is a reference to the respective order.
8. The method of any one of claims 1 to 7, wherein said data model comprises an order in which a plurality of said activities within said order constitutes an operation, and wherein each operation has a pre-assigned operation number, said data model further comprising a database table having an entry for each object identity and pre-assigned operation number matched to the earliest activity of the respective operation.
9. The method of any one of claims 2 to 8, wherein each material has a pre-assigned material number, said data model further comprising a database table having an entry for each pre-assigned material number matched to a reference to at least one input interface node at which the respective material is consumed, and an entry for each pre-assigned material number matched to a reference to at least one output

interface node at which the respective material is created.

10. The method of claim 9, wherein said database table further comprises identifying information for each material including at least one of plant, storage location, and batch.
11. The method of any one of claims 2 to 10, wherein each resource has a pre-assigned resource number, said data model further comprising a database table having an entry for each pre-assigned resource number matched to a chronological sequence of activities scheduled on the respective resource.




FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5a

FIG. 5b






FIG. 6






FIG. 9




FIG. 10




FIG. 11

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/01346

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G06F17/60

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 303 144 A (KAWASHIMA KAZUHIRO ET AL) 12 April 1994 see column 1, line 45 - column 2, line 45 see column 4, line 12 - column 6, line 62 see column 8, line 33 - line 47 see column 10, line 55 - column 11, line 16 see figures 5,6,15A-B see figures 16A-B,19A-B see figures 27A-B,28A-B ----	1,3-5,7, 8,10
Y	---- -/-	2,6,9,10

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
5 July 1999	15/07/1999
Name and mailing address of the ISA	Authorized officer
European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl. Fax: (+31-70) 340-3016	Pedersen, N

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 99/01346

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	<p>FOURER R: "Database structures for mathematical programming models" DECISION SUPPORT SYSTEMS, AUG. 1997, ELSEVIER, NETHERLANDS, vol. 20, no. 4, pages 317-344, XP002108169 ISSN 0167-9236 see abstract see page 324, column 2, line 33 - page 326, column 1, line 11 see page 328, column 2, line 16 - page 330, column 1, line 8</p> <p>---</p>	2,6,9,10
A	<p>WO 97 00488 A (I2 TECHNOLOGIES INC) 3 January 1997 see page 3, line 1 - page 5, line 25 see page 8, line 1 - page 11, line 20 see figure 1</p> <p>---</p>	1-11
A	<p>GB 2 302 427 A (I2 TECHNOLOGIES INC) 15 January 1997 see page 4, line 10 - page 5, line 12 see figure 1</p> <p>---</p>	1-11
A	<p>US 5 229 948 A (WEI KUANG C ET AL) 20 July 1993 see column 4, line 37 - line 62 see figure 1</p> <p>---</p>	1-11
A	<p>US 5 331 545 A (YAJIMA HIROSHI ET AL) 19 July 1994 see column 3, line 15 - column 4, line 13 see column 7, line 30 - line 37 see figure 9</p> <p>-----</p>	1-11

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/01346

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
US 5303144	A	12-04-1994	JP	3180963 A		06-08-1991
WO 9700488	A	03-01-1997	US	5764543 A		09-06-1998
			AT	174705 T		15-01-1999
			AU	5598996 A		02-01-1997
			BR	9608596 A		05-01-1999
			CA	2176531 A		17-12-1996
			DE	69601152 D		28-01-1999
			DE	69601152 T		20-05-1999
			EP	0776507 A		04-06-1997
			ES	2128172 T		01-05-1999
			GB	2302426 A		15-01-1997
			JP	9016686 A		17-01-1997
GB 2302427	A	15-01-1997	AT	175045 T		15-01-1999
			AU	5599096 A		02-01-1997
			CA	2176530 A		17-12-1996
			DE	69601208 D		04-02-1999
			DE	69601208 T		20-05-1999
			EP	0776509 A		04-06-1997
			ES	2128177 T		01-05-1999
			JP	9006862 A		10-01-1997
			WO	9700489 A		03-01-1997
US 5229948	A	20-07-1993		NONE		
US 5331545	A	19-07-1994	JP	5189450 A		30-07-1993